

BELIZE E2 – EFFEKTBEREGNING

Drift	Statisk				Komfort			Boost		
Type	22				22			22		
Høyde	500		600	900	500	600	900	500	600	900
Lengde	Syst.temp	W	W	W	W	W	W	W	W	W
400	60/45/20	308	351	448	448	482	580	513	546	655
	55/45/20	282	322	411	414	446	538	481	506	607
	45/35/20	163	184	233	252	272	324	294	317	375
	35/30/20	89	100	126	149	162	189	176	189	225
600	60/45/20	462	527	673	671	724	869	769	819	982
	55/45/20	424	484	617	622	670	808	721	760	910
	45/35/20	245	276	349	379	409	486	440	475	562
	35/30/20	134	150	188	224	242	284	263	284	337
800	60/45/20	616	702	897	895	965	1159	1025	1092	1309
	55/45/20	565	645	822	829	893	1077	961	1013	1214
	45/35/20	327	368	466	505	545	648	587	634	750
	35/30/20	179	200	251	298	323	378	351	378	450
1000	60/45/20	770	878	1121	1119	1206	1449	1282	1365	1637
	55/45/20	706	806	1028	1036	1116	1346	1201	1266	1517
	45/35/20	409	460	582	631	681	810	734	792	937
	35/30/20	224	250	314	373	404	473	439	473	562
1200	60/45/20	924	1054	1345	1343	1447	1739	1538	1638	1964
	55/45/20	847	967	1234	1243	1339	1615	1442	1519	1820
	45/35/20	490	552	698	757	817	972	881	950	1124
	35/30/20	268	300	377	448	485	568	527	568	674
1400	60/45/20	1078	1229	1569	1566	1689	2029	1794	1911	2291
	55/45/20	988	1128	1439	1450	1562	1884	1682	1772	2124
	45/35/20	572	644	815	883	953	1134	1028	1109	1312
	35/30/20	313	350	440	522	566	662	615	662	787
1600	60/45/20	1232	1405	1793	1790	1930	2319	2050	2185	2619
	55/45/20	1130	1290	1645	1658	1786	2154	1922	2026	2427
	45/35/20	654	736	931	1010	1090	1296	1174	1267	1499
	35/30/20	358	400	502	597	646	757	702	757	899
1800	60/45/20	1386	1580	2018	2014	2171	2608	2307	2458	2946
	55/45/20	1271	1451	1850	1865	2009	2423	2163	2279	2731
	45/35/20	735	828	1048	1136	1226	1458	1321	1426	1687
	35/30/20	402	450	565	671	727	851	790	851	1012
2000	60/45/20	1540	1756	2242	2238	2412	2898	2563	2731	3273
	55/45/20	1412	1612	2056	2072	2232	2692	2403	2532	3034
	45/35/20	817	920	1164	1262	1362	1620	1468	1584	1874
	35/30/20	447	500	628	746	808	946	878	946	1124

Forklaring syst.temp: Eks = $\frac{\text{Fremløp temp.}}{45} / \frac{\text{Returtemp.}}{35} / \frac{\text{Rom temp.}}{20}$